



Implementation Guidelines for ISO 20022 Interbank Messages

SIC and euroSIC

Cash Management Receipts (camt.025)

Version 2.4, valid from 21 November 2025

Change history

All the changes carried out in this document are listed below with the version number, the change date, a brief description of the change and references to the chapters affected.

Version	Date	Description of the change	Chapter
2.4	28.02.2025	Modifications per SIC Platform Release 4.12	
		Modifications of "Technical specifications for the RTGS service": Addition of a reference to the base document due to changed specifications for "ISODateTime" (CR2025-SIC4-0002) for the following element: <ul style="list-style-type: none"> <i>MsgHdr/CreDtTm</i> 	4.1
2.3	28.02.2024	Correction in chapter "Naming of the parties": Also in the case of acknowledgment by the participant to the RTGS, the party must correspond to the sending participant of the message to be acknowledged (correction of inconsistency, the <i><OrgtrNm></i> element definition according to chapter 4.2 corresponds unchanged to the current system behavior)	3.3
2.2	22.05.2023	Errata per SIC Platform Release 4.10	
		Correction of the element name <i>.../OrgnlMsgId/MsgNmId</i> (formerly incorrect <i>.../OrgnlMsgId/OrgnlMsgNmId</i>)	3.1, 3.5
2.1	28.02.2023	Modifications per SIC Platform Release 4.10	
		New CH schema version camt.025.001.05.ch.02.xsd (Details according to separate document "Overview and Change Log for the XML schemas")	1.4
		Additions to and editorial revision of notes in chapter "General" (clarification of current system behaviour, no functional change)	3.1
		Addition of the elements filled with UNKNOWN in chapter "Acknowledging messages that cannot be validated" (clarification of current system behaviour, no functional change)	3.5
		<i>.../RctDtls/OrgnlMsgId/MsgNmId</i> : modification of the permitted format of message types (alignment with acknowledgement message pacs.002)	4.2
2.0	30.11.2021	Complete revision due to update of ISO 20022 version 2019	All
		New "Introduction" chapter (replaces and includes the previous "Overview of the documentation structure" chapter and annexes).	1
		New ISO 20022 schema version	1, 2
		Changed definition from SWIFT MX to ISO 20022	2
		Revision of "Technical specifications for the RTGS services": <ul style="list-style-type: none"> New codes SIC/SEU for identification of the clearing system in the <i>.../MsgHdr/ReqTp/Prtry/Id</i> element 	4.1
1.4	28.02.2020	Last edition based on previous ISO 20022 version status	
1.0	21.03.2016	First edition	All

Table 1: Change history



Please address all suggestions, corrections, and proposed improvements to this document to:

SIX Interbank Clearing Ltd

Hardturmstrasse 201

CH-8005 Zurich

E-Mail: contact.sic@six-group.com

www.six-group.com

General notes

SIX Interbank Clearing Ltd ("**SIC Ltd**") reserves the right to modify this document, as the need arises, at any time without prior notice.

SIC Ltd reserves all rights for this document including the rights of photomechanical reproduction, storage on electronic media and the translation into foreign languages.

Although great care has been taken in the compilation and preparation of this work to ensure accuracy, errors and omissions cannot be entirely ruled out. SIC Ltd cannot be held liable for any decision made or action taken in reliance on the information in this document or for any consequential, special or similar damages.

To improve readability, the use of masculine and feminine forms of language are avoided wherever possible. All personal designations are to be regarded as gender neutral.

If you detect any errors in this document or have any ideas or suggestions for improvements, we would be extremely grateful if you would notify these by e-mail to contact.sic@six-group.com.

Table of contents

Change history	2
General notes	4
Table of contents	5
Table of tables	6
Table of figures.....	7
1 Introduction.....	8
1.1 Overview of the documentation structure	8
1.2 Target audience.....	9
1.3 Change control	9
1.4 XML schema	9
1.5 Validation portal	9
1.6 Reference documents	9
2 ISO definitions	10
3 Business specifications for the RTGS services	11
3.1 General	11
3.2 References in the "Receipt" message (camt.025)	12
3.3 Naming of the parties	13
3.4 Transaction status.....	14
3.5 Acknowledging messages that cannot be validated	15
3.6 Error codes	15
3.7 Further business specifications.....	15
4 Technical specifications for the RTGS services.....	16
4.1 Message Header (MsgHdr, A-level)	16
4.2 Receipt Details (RctDtls, B-level).....	18

Table of tables

Table 1:	Change history	2
Table 2:	Permitted status values in the ReqHdlg/StsCd element	14
Table 3:	Message Header (MsgHdr, A-level)	17
Table 4:	Receipt Details (RctDtls, B-level).....	20

Table of figures

Figure 1:	Documentation structure for message type "camt.025"	8
Figure 2:	Basic message structure of the "camt.025" message	10
Figure 3:	Acknowledgement of a cash management message by the RTGS services	11
Figure 4:	Acknowledgement of a cash management message by the participant	11
Figure 5:	References in the "camt.025" message	12
Figure 6:	Details of participants	13
Figure 7:	Indicating the transaction status	14
Figure 8:	Indicating the error code and XPath in an acknowledgement by the RTGS services	14
Figure 9:	Message Header (MsgHdr)	16
Figure 10:	Receipt Details (RctDtls)	18

1 Introduction

1.1 Overview of the documentation structure

The Implementation Guidelines consist of a base document with general information concerning all message types, and various module documents – this document is for the message type "camt.025" – with message-specific information, including information on the application-specific handling of individual elements. They specify the messages to be submitted to and delivered from the RTGS services SIC and euroSIC using the ISO 20022 message standard.

These Implementation Guidelines are modular in structure:

- The base document contains general information applying to all messages.
- The module documents contain message-specific information, including information on the application-specific handling of certain elements.
- For each Implementation Guideline, an XML schema (XSD) and generic XML sample messages will be published.




Figure 1: Documentation structure for message type "camt.025"

1.2 Target audience

The "Implementation Guidelines for ISO 20022 Interbank Messages" are addressed to all participants of the Swiss RTGS services SIC and euroSIC.

1.3 Change control

All modifications made to this document are listed in the change history showing the version, the date of the change, a brief description and references to the chapters concerned.

1.4 XML schema

The XML schema for "camt.025" is published on the www.iso-payments.ch website.

- ***camt.025.001.05.ch.02.xsd***

It should preferably be opened using specialized XML software.

1.5 Validation portal

After registration, users can upload their own messages to the SIC & euroSIC Validation Portal Interbank Messages (validation.iso-payments.ch/SIC4) and validate them against these Implementation Guidelines.


1.6 Reference documents

Additional information on the Implementation Guidelines can be found in the reference documents listed in the Base document.

2 ISO definitions

The "Receipt" message (camt.025) is sent from the participant to the RTGS services and from the RTGS services to the participant, to acknowledge that a camt message has been received.

The "Receipt" message is based on the ISO 20022 XML schema "camt.025.001.05".



The "camt.025" message is essentially structured as follows:

- **A-level:** Message level, "Message Header" element. This block must occur exactly once.
- **B-level:** Transaction level, "Receipt Details" element. This block must occur exactly once.

Figure 2: Basic message structure of the "camt.025" message

3 Business specifications for the RTGS services

3.1 General

The "Receipt" message is used in the RTGS services for acknowledging cash management messages (information and control messages) as follows:




Figure 3: Acknowledgement of a cash management message by the RTGS services




Figure 4: Acknowledgement of a cash management message by the participant

Notes:

- All camt messages will be acknowledged with "camt.025".
- For a successful OK acknowledgement (camt.025 with status ACCP) from the participant to the RTGS services, the following element contents must match the corresponding attributes of the acknowledged message:
 - *RctDtls/OrgnlMsgId/MsgId* (original message identification)
 - *RctDtls/OrgnlMsgId/MsgNmId* (original message name identification)
 - *RctDtls/OrgnlMsgId/OrgtrNm* (member identification, not mandatory for all acknowledged message types, details according to element definition in chapter 4.2)
- NOK acknowledgements (camt.025 with status RJCT) from the participant to the RTGS services may only be sent in the event of an authentication error of the received message.
- SWIFT InterAct messages received via the SWIFT gateway must not be acknowledged by the participant.

3.2 References in the "Receipt" message (camt.025)

Along the processing chain, two references are sent in the "camt.025" message:

A-level: MsgHdr/MsgId – unique message identification for the "camt.025" message

B-level: RctDtls/OrgnlMsgId/MsgId – message identification for the acknowledged message




Figure 5: References in the "camt.025" message

3.3 Naming of the parties

In the "camt.025" message, in the *RctDtls*/*OrgnlMsgId*/*OrgtrNm* element, in the case of an acknowledgement from the RTGS services to the participant, the participant is identified who sent the message to be acknowledged. Also in the case of an acknowledgement from the participant to the RTGS services, the sending participant of the message to be acknowledged has to be supplied (details according to the element definition in chapter 4.2).




Figure 6: Details of participants

3.4 Transaction status

The transaction status of the message being acknowledged is shown in the "camt.025" message in the `<ReqHdlg>` element. This element must be sent once and may only contain the sub-element `<StsCd>`:




Figure 7: Indicating the transaction status

The following status values are provided for in the `ReqHdlg/StsCd` element:

Code	Description
ACCP (Accepted Customer Profile)	Received message is correct.
RJCT (Rejected)	Received message cannot be validated.

Table 2: Permitted status values in the `ReqHdlg/StsCd` element

In the case of a NOK acknowledgement from the RTGS services to the participant, further instances of the `<ReqHdlg>` element are sent which each contain a 3-digit error code as per the SIC/euroSIC Handbook in the `<StsCd>` element and also, in the `<Desc>` element, the Xpath for the incorrect element in the message being acknowledged:




Figure 8: Indicating the error code and XPath in an acknowledgement by the RTGS services

3.5 Acknowledging messages that cannot be validated

If a message that is sent cannot be validated for technical reasons, this is confirmed by the RTGS services with a generic NOK message.

To show the status of the message, the code RJCT is entered in the sub-element *<StsCd>* in the first instance of the *<ReqHdlg>* element.

In a second instance of the *<ReqHdlg>* element, the SIC error code "118" is entered in the *<StsCd>* sub-element (see section 3.6) and "n/a" in the *<Desc>* sub-element.

At the same time, the following mandatory elements will be filled with the value UNKNOWN:

- *RctDtls/OrgnlMsgId/MsgId* (original message identification)
- *RctDtls/OrgnlMsgId/MsgNmId* (original message name identification)
- *RctDtls/OrgnlMsgId/OrgtrNm* (member identification)

Note about schema violations

If a message that is sent cannot be validated due to a schema violation, the SIC error code "221" is used in a similar procedure as described in this section.

3.6 Error codes

In the "camt.025" message, the 3-digit error codes are used in accordance with the SIC/euroSIC Handbook.

3.7 Further business specifications

Further business specifications can be found in the Base document.

4 Technical specifications for the RTGS services

4.1 Message Header (MsgHdr, A-level)

The "Message Header" (A-level of the message) occurs exactly once in the message and contains the following elements:




Figure 9: Message Header (MsgHdr)

The following table specifies all the elements of the "Message Header" of the "camt.025" message that are relevant in the context of the RTGS services.

ISO 20022 Standard			Swiss ISO 20022 Payments Standard	
Message Item	XML Tag	Mult	Mult	Definition
Document +Receipt V05	Rct	1..1	1..1	
Message Header	MsgHdr	1..1	1..1	
Message Header +Message Identification	MsgId	1..1	1..1	Message Identification Only the restricted character set for references (excluding spaces) is permitted for this element.
Message Header +Creation Date Time	CreDtTm	0..1	1..1	Creation Date Time See chapter "Times in all services (ISODateTime)" in the Implementation Guideline "Base Document".
Message Header +Request Type	ReqTp	0..1	1..1	
Message Header +Request Type ++Proprietary	Prtry	1..1	1..1	
Message Header +Request Type ++Proprietary +++Identification	Id	1..1	1..1	Clearing System Identification (proprietary) Identification of the clearing system, the following code values are available: SIC (CHF only) = value SIC must be used euroSIC (EUR only) = value SEU must be used

Table 3: Message Header (MsgHdr, A-level)

4.2 Receipt Details (RctDtls, B-level)

The "Receipt Details" (B-level of the message) contains the information about the message being acknowledged.




Figure 10: Receipt Details (RctDtls)

The following table specifies all elements of the "Receipt Details" of the "camt.025" message that are relevant in the context of the RTGS services.

ISO 20022 Standard			Swiss ISO 20022 Payments Standard	
Message Item	XML Tag	Mult	Mult	Definition
Receipt Details	RctDtIs	1..n	1..1	
Receipt Details +Original Message Identification	OrgnIMsgId	1..1	1..1	
Receipt Details +Original Message Identification ++Message Identification	MsgId	1..1	1..1	Original Message Identification If the message identification of the message being acknowledged is not available, fill in with the value UNKNOWN.
Receipt Details +Original Message Identification ++Message Name Identification	MsgNmId	0..1	1..1	Original Message Name Identification The first 8 digits of the message type must mandatory be present. The following values are permitted (will be validated by the RTGS service): <ul style="list-style-type: none"> • camt.007 • camt.008 • camt.019 • camt.027 • camt.029 • camt.048 • camt.050 • camt.052 • camt.054 • camt.056 • camt.087 The element contains UNKNOWN if the type of the original message could not be identified. Additional digits to indicate the complete message version (e.g. "camt.019.001.07") are permitted but will not be validated by the RTGS service.

ISO 20022 Standard			Swiss ISO 20022 Payments Standard	
Message Item	XML Tag	Mult	Mult	Definition
Receipt Details +Original Message Identification ++Originator Name	OrgtrNm	0..1	0..1	Member Identification If the element <MsgNmId> contains the value camt.007, camt.008, camt.027, camt.029, camt.048, camt.050, camt.056 or camt.087 this element must be provided. For all other message types, the element may be omitted. If provided, the content of this element will be ignored. For camt.050 the information can be obtained from Dbtr/FinInstnId/ClrSysMmbId/MmbId, for camt.007 the information can be obtained from the provided sub-element of ModfyTx/Mod/PmtId/LngBizId/InstgAgt/FinInstnId, for camt.008 the information can be obtained from the provided sub-element of CclTx/PmtId/LngBizId/InstgAgt/FinInstnId, for camt.048 the information can be obtained from the provided sub-element of ModfyRsvatn/RsvatnId/Cur/AcctOwnr/FinInstnId, for camt.027, camt.029, camt.056 and camt.087 the information can be obtained from the provided sub-element of Assgnr/Agt/FinInstnId. The element contains UNKNOWN if the type of the original message could not be identified.
Receipt Details +Request Handling	ReqHdlg	0..n	1..n	Status Reason Information At least one <ReqHdlg> block must be created to show the transaction status of the received message. Message from participant to RTGS service: Exactly one <ReqHdlg> block must be present. NOK message from RTGS service to participant: One additional <ReqHdlg> block containing information about the reason for rejection will be created for each identified error.
Receipt Details +Request Handling ++Status Code	StsCd	1..1	1..1	Transaction Status or Status Report Reason The following ISO codes are used to indicate the transaction status of the received message: ACCP = Received message is correct. RJCT = The message contains errors and could not be processed. Can only be sent in messages from the participant to RTGS in case of an error in the authentication of the received message. NOK message from the RTGS service to the participant: Proprietary 3-digit SIC error codes will be provided in this element within an additional <ReqHdlg> block for each identified error. Error codes in accordance with the SIC / euroSIC Handbook.
Receipt Details +Request Handling ++Description	Desc	0..1	0..1	Erroneous Element Location of the incorrect element as an XPath. Use only permitted in NOK messages from the RTGS service to participants. Must not be used in the <ReqHdlg> instance containing the transaction status (ACCP/RJCT). "n/a" will be provided if the error cannot be unambiguously assigned to one element.

Table 4: Receipt Details (RctDtls, B-level)